

Push Button Emergency Station

The palm-size Akuvox E20S Push Button Emergency Station is ruggedized with 316-grade stainless steel. E20S can be used on 1299 and 86 type single in-wall box.



At a Glance

- Vandal resistant body, with a panic button;
- PoE (IEEE802.3af, Power-over-Ethernet);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Support advanced group conference call features;
- Complies with SIP standard for easy integration in every SIP capable PBXes;
- For indoor use only;

Physical & Power

- Front panel: 316 grade stainless steel
- Button: 1 panic button
- Ethernet port: RJ45, 10/100Mbps adaptive
- Power supply: PoE (IEEE802.3af) only
- Indicator: 1
- Microphone / Speaker: 1 / 1
- Dimensions: 100x100x38 mm
- Installation: Flush-mounted
- Working Humidity: 10~90%
- Working Temperature: -20°C ~ +55°C
- Storage Temperature: -25°C ~ +60°C
- SIP Protocol: SIP v1 (RFC2543), SIP v2 (RF3261)
- SIP account: 1 SIP account
- Audio codecs: G.711a, G.711μ, G.722
- QoS support: Yes
- Auto Answer support: Yes
- Network mode: DHCP or Static IP
- System time: NTP for auto time setting
- Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTP, TCP, UDP, ICMP, DHCP, ARP