

iCode 03 Slim®

Datasheet



The following rights are reserved:

- Any unannounced changes to the functionality or appearance of this product will void the warranty.
- Use of this product in any environment or in any manner not specified herein will also void the warranty.



Features	ICODE03 ANSI Slim
Material	304 Stainless steel
Opening Method	Code , RFID card, WiFi, BLE,APP, Mifare (13,56MHz)
Identification Time	<1.5S
Communication	Bluetooth 4.1
Cylinder	ANSI
Compatibility with	ANSI Standard US
Emergency Power	USB C
Emergency Opening	Mechanical key
Power	6 Volts - 4 alkaline batteries 3 A (1,5v x 4)
Max. Power	6 V-MAX
Battery Life	+/- 5000 cicles
Leds	White
Low Battery Alarm	Led flashes, voice prompt, APP
Consumption	<200mA
Static Consumption	80 mA
Open Time	5s; 10s; 15S; 30s; 60s; Personalized
Software Windows	iTEC Hybrid
Software WEB APP's	ITEC ON ACCESS PRO , Hospitalaty
	iTEC iOA
	iTEC iOA PRO
	IOS 8 and above
	Android 5 and above
Stand Alone	yes
IP	IP54
Weight	3 kgs
Moisture Resistance	10%-95%
Operating Temp.	- 20 C~+70C
Code (nr digits)	4 ~ 9
Code No. via APP	Unlimited
Code No. self-defined	150
Fingerprint No.	NA
IC Card No.	200
Available Colors	Black, SS Satin
Installation	Residences, Apartments,
	Residential, Offices,
	AIRBNB, Hotels
Door thickness	45mm ~110mm



Web: GlobalVisionsInc.com
Email: sales@GlobalVisionsInc.com
Phone: 877-725-8869